

FARM PICK UP - 4 AXLES

QUALITY AND DURABILITY



SERVICE CENTRES

TREMCAR

HEAD OFFICE

790, Montrichard Avenue
St-Jean-sur-Richelieu, Québec
Canada J2X 5G4

Phone: (450) 347-7822

or (800) 363-2158

Fax: (450) 347-8372

TREMCAR

SALES & SERVICE CENTER:

2060 Oxford Street E.
London, Ontario
Canada N5V 2Z8

Phone: (519) 452-7732

Fax: (519) 452-4861

TREMCAR.COM

Technical specifications

Code	Sanitary
Working pressure / temp	Atmospheric 180 ° F
Shape	Round, cleanbore or elliptical
Number of compartment	2
Capacity	34 000 to 41 000 L
Inner tank	T 304 stainless steel – 2B, W5 Dairy Grade Welds
Head	T 304 stainless steel – 2B, W5 Dairy grade Welds
Reinforcing ring	Stainless steel top hat section or compression fit
Insulation	High density styrofoam 3" thickness, heads and underside with fiberglass
Frame	T304 stainless steel with boxed cross members/outriggers
Outer shell	Prebuff 22 ga
Outer head	Front: T304 stainless steel - #4 finish – lockformed Rear: T304 stainless steel - #4 finish - welded
Outlet valve	3 – 3" sanitary butterfly valve with manifold
Manhole	Tremcar 4 lugs – complete with dust cover and sanitary gasket
Vent	Two Rhinovent per manhole
Rear cabinet	Full size FPU
Pump	USFIP 2-1/2"
Motor	3 hp – farm duty
Washing system	2 Klenzade balls each compartment, with one inlet 2" ACME
Sanitary hose	33' X 2-1/2" milk hose
Fender	Stainless Steel
Mudflap	Tremcar – white mudflaps
Ladder	Two stainless steel ladders
Walkway	Aluminum Diamond Grip
Suspension	Intraax AA250T and Hendrickson Connex-ST self steer
Axles	Included with Hendrickson
Hubs and drum	Steel hub, 10 stud, hub pilot, cast drum
Wheel	8.25 X 22.5 Steel disc, 10 holes, hub-piloted and 12.25 x 22.5 wide base
Brakes	16.5" X 7" quick change with 4S/2M Meritor ABS system
Tires	Yokohama
Nose box	Tremcar – T304 with seven way receptacle
Fifth wheel plate	Bolted, adjustable, heavy duty plate
Landing gear	Jost, 160 000# - 2 speeds
Lights and wiring	Grote wiring and lighting system
Bumper	Heavy duty 4" X 4" stainless steel clad steel tubing
Paint	Primed and painted, mild steel parts only

Options and substitutions to standard



Distributed by