

ALUMINUM TANDEM AXLE PETROLEUM SEMI TRAILER

QUALITY AND DURABILITY



SERVICE AND PRODUCTION FACILITIES

TREM CAR USA INC.

436 - 12th Street N.E.
Strasburg, OH 44680
Phone: (330) 878-7708
or (888) 873-6227
Fax: (330) 878-5074

BOSTON STEEL

89, Newark St.
Haverhill, MA 01832, USA
Phone: (978) 556-5330
Fax: (978) 556-5315

TREM CAR INC.

HEAD OFFICE
790, Monrillard Ave.
Saint-Jean-sur-Richelieu
QC, Canada J2X 5G4
Phone: (450) 347-7822
or (800) 363-2158
Fax: (450) 347-8372

TREM CAR.COM



Technical specifications

Code	DOT-406
Capacity	9200 USG
Design	Elliptical double tapered or straight elliptical design
Tank Frame	Extruded aluminum sills, pads, outriggers & crossmembers
Manhole Covers	Aluminum 16"
Outlet Valves	4" aluminum air operated emergency valve with operator & emergency release valve
Bottom Loading	Discharge are 4" openable API adaptors
Overfill	Thermo-optic sensors and socket in a protective box
Brake Interlocks	On bottom load adaptor and vapor recovery adaptor
Vapor Recovery	3 1/2" vents with hoods and piped to vapor rail
Cabinet	Aluminum
Fenders	Aluminum with white mudflaps
Ladder	Aluminum at front head
Bumper	Aluminum to DOT-406 regulations
Lights & Wiring	Grote wiring, Supernova or Next Gen with LED wiring
Nose Box	7-prong plus and air connections 18" lower quadrant driver's side
Landing Gear	2 speeds, 160 000 lbs rating
Suspensions & Axles	Intraax AATN 23K/Hendrickson Hendrickson Intraax AANT23K
Wheels	Aluminum disc wheels 10 hole-hub piloted
Tires	11R22.5, 14 or 16 ply
Brakes	16 1/2" x 7" FMVSS standards
Painting	Steel parts sandblasted, primed and painted urethane
Accessories	Full length aluminum hose tray on c/s in lieu of fenders Placard holders Conspicuity markings as required by regulations

Options and substitutions to standard

Distributed by

