PETROLEUM TC-406 B-TRAIN











SERVICE CENTRES

TREMCAR WEST INC.

(Edmonton) 1750, Aurum Road, Edmonton

AB, Canada T6S 0A4 Phone: (780) 371-1579 or (855) 552-8880 Fax: (780) 317-2524

TREMCAR WEST INC.

TREMCAR WEST INC (Weyburn)

216 - 20th Avenue S.E. Box 964

Weyburn

SK, Canada S4H 2L2

Phone: (306) 842-6100 Fax: (306) 842-6101

TREMCAR WEST INC.

(Saskatoon) 202 Melville Street Saskatoon

SK, Canada S7J 0R1 Phone: (306) 931-9777

Fax: (306) 931-9778

TREMCAR.COM

Technical specifications

Code Capacity Design

Cabinet

Fenders Ladder

Upper wheel plate

Rear deck of lead

Suspensions & Axles

Landing Gear

Wheels

Tires

Brakes

Painting

Accessories

TC-406 specifications

33.000 Litre Lead Trailer and 29.500 Litre Rear Trailer Elliptical in 3/16" and 1/4" Aluminium alloy 5454-H32

bright finish side

Heads are dished and flanged Aluminium alloy 5454-HO bright finish

Max. temperature 50 degrees Celsius

Tank Frame Extruded aluminium sills, outriggers and crossmembers Manhole Covers

Tiona de luxe PAF 406-98 assemblies 20"

Outlet Valves Betts 4" alum, air operated emergency valves with operator and

emergency release valve.

Bottom Loading Discharge through 4" openable adaptors, Scully thermo-optic

sensors and Scully socket in a protective box

Vapour Recovery Betts 3 1/2" vents with hoods and piped to vapour rail

Aluminium 42" x 28" x 34" one on each trailer

Stainless steel polished

Aluminium at rear with Gripstrut step

Bumper On rear unit only, Alum, to TC-406 requirements Lights & Wiring

Grote wiring and Light system

Nose Box 7-way plug and air connections 18" up front head centre Fall restaint Lanvard fall restraint system on inside of overturn rail

> Heavy Duty 3/8" steel Bolted to frame Jost A450 Magnum with sand shoes

Intraax

Aluminium LVL wheels 10 hole-hub piloted

11R22.5, AEOLUS HN06, 16 plies

16 1/2" x 7" to FMVSS standards Wabco

Steel reinforced 'B' frame with Kompensator Fifth Wheel Steel parts sandblasted, primed and painted urethane black

Two -7" x 21 foot Alum. hose tubes on each trailer

1202/1203/3475

Conspicuity Markings as required by Transport Canada Fire extinguisher in a polypropytene box on each trailer

Options and substitutions to standard

Distributed by