

PNEUMATIC - 1625 CUBIC FEET VACUUM - 2 AXLES

QUALITY AND DURABILITY



SERVICE CENTERS

TREM CAR USA INC.
SALES & SERVICE CENTER:
436 - 12th Street N.E.
Strasburg, OH 44680, USA
Phone: (330) 878-7708
or (888) 873-6227
Fax: (330) 878-5074

BOSTON STEEL
SALES & SERVICE CENTER:
89, Newark St.
Haverhill, MA 01832, USA
Phone: (978) 556-5330
Fax: (978) 556-5315

TREM CAR INC.
HEAD OFFICE:
790, Montrichard Ave.
Saint-Jean-sur-Richelieu
QC, Canada J2X 5G4
Phone: (450) 347-7822
or (800) 363-2158
Fax: (450) 347-8372

TREM CAR.COM



Technical specifications

Model Construction	Dry bulk - 1 625 cubic feet Vacuum Smooth aluminum exterior with internal flat bar-type bracing, internal hopper apex reinforcing plates.
Framing	Aluminum front and rear
Working pressure	MAWP 15 PSIG, 13" Hg Vac. Temp. 180°F.
Internal finish	Class II finish; compatible with plastic and sanitary applications.
Manhole	4 - 20" full opening, cast aluminum cover with 6 CAM-type hold down and white rubber gasket.
Cooling unit	Provides cooled air to prevent product damage. The installation comes with appropriate filtration units to protect the blower.
Discharge valve	5", driver's side operation with 5" X 4" aluminum Sure Seal tees
Rear external filter	30" Aluminum canister offset to roadside with access platform.
Fill line	6" aluminum, at rear.
Piping	4" aluminum SCH 40 pipe between hoppers and aluminum SCH 40 pipe from last hopper to the rear.
Air inlet	4" aluminum adapter with dust cap located at front driver's side elled upward
Gauge	4", gauges for tank, line and vacuum pressure in an aluminum box.
Ladder	Aluminum with 1 1/4" diam. Riser tuding, anti-slip rungs, and top step offset to curbside with platform for access to canister.
Catwalk	Two (2) platforms to access canister and air actuated valve.
Hose tube	Two (2) Aluminum, 8" X 21", with rear cast doors
Light	Center marker lights wired to turn signals
Light boxe	Stainless steel
Suspension	Intraax AAT250T
Axle	Included with Intraax
Brake	Air actuated 16.5" X 7" S-cam quick change, TSE 30/30 chambers with Meritor automatic slack adjusters and Meritor 4S/2M ABS system
Hubs and drum	10-Hole Conmet hub-piloted aluminum hubs with preset bearings and outboard mounted centrifuse drums
Wheel	8.25 X 22.5 aluminum disc, 10 holes, hub-piloted
Tire	11R 22.5 14 PLY
Landing gear	Jost A-400, 160 000# -2 speed
Fifth wheel plate	3/8" thick plate adjustable to every 2"
Fender	Rolled aluminum

Options and substitutions to standard



Distributed by