

**DRY BULK - 1850 CUBIC FEET  
4 AXLES**

**QUALITY AND DURABILITY**



## **SERVICE CENTRES**

**TREMCAR**  
HEAD OFFICE  
790, Montrichard Avenue  
St-Jean-sur-Richelieu, Québec  
Canada J2X 5G4  
Phone: (450) 347-7822  
or (800) 363-2158  
Fax: (450) 347-8372

**TREMCAR**  
SALES & SERVICE CENTER:  
2060 Oxford Street E.  
London, Ontario  
Canada N5V 2Z8  
Phone: (519) 452-7732  
Fax : (519) 452-4861

**TREMCAR.COM**



## Technical specifications

<b>Model</b>	1 850 cubic feet, Pneumatic Dry Bulk
<b>Construction</b>	Smooth aluminum exterior with internal bar-type bracing, internal hopper apex reinforcing plates
<b>Framing</b>	Aluminum front and rear
<b>Pressure</b>	MAWP 15 PSIG
<b>Internal finish</b>	Compatible with cement, lime and sand
<b>Manhole</b>	4 - Knappco, 20" full opening, cast aluminum cover with 6 CAM-type latches and white food-grade gasket.
<b>Discharge valve</b>	5" BTI, driver's side operation with 6" X 5" aluminum BTI tees
<b>Bottom aeration</b>	BTI Siphon Flow Aerators
<b>Air inlet</b>	3" aluminum adapter with dust cap located at front driver's side angled upward
<b>Gauge</b>	4" silicone filled gauges for tank and line pressure
<b>Ladder</b>	Aluminum, mounted at rear
<b>Catwalk</b>	24" aluminum grip from rear ladder to front manhole
<b>Hose tube</b>	Aluminum 8" x 21' with rear cast doors
<b>Light</b>	Grote, center marker lights wired to turn signals
<b>Light box</b>	Tremcar, stainless steel
<b>Suspension</b>	Intraax AA250T ( et non 230 )
<b>Axle</b>	Included with Intraax
<b>Brake</b>	Air actuated 16.5" X 7" X ¾" S-cam quick change style 30/30 Meritor automatic slack adjusters and Meritor 4S/2M ABS system
<b>Hubs and drum</b>	10-Hole hub-piloted steel hubs with pre-greased bearings and outboard mounted cast drums
<b>Wheel</b>	8.25 X 22.5 steel disc, painted white, 10 holes, hub-piloted
<b>Tire</b>	Yokohama
<b>Landing gear</b>	Jost A-400, 160 000#
<b>Fifth wheel plate</b>	3/8" thick plate adjustable to every 2"
<b>Fender</b>	Rolled aluminum, bolt-on aluminum supports

## Options and substitutions to standard

Distributed by